

Display



Date: November 16, 1998 Subject: MANUAL CORRECTION—SET-UP

ADJUSTMENTS

Model: PVM-14N1U, PVM-14N2U, PVM-20N1U PVM-20N2U, SSM-14N1U, SSM-20N1U

Serial No: **SEE TEXT**

DESCRIPTION

Correct the PVM-14N1U, PVM-14N2U, SSM-14N1U, PVM-20N1U, PVM-20N2U, SSM-20N1U Service Manual (Rev. 3) as shown in Figure 1.

This bulletin affects units with the following serial numbers:

PVM-14N1U 6,000,001–6,003,583 PVM-14N2U 6,000,001–6,002,319 PVM-20N1U 6,000,001–6,001,487 PVM-20N2U 6,000,001–6,000,847 SSM-14N1U 6,000,001–6,002,571 SSM-20N1U 6,000,001–6,000,967

SECTION 3
SET-UP ADJUSTMENTS
SETTING FOR EACH COLOR STANDARD

NO.	DISP.	ITEM	NTSC 358			NTSC	PAL	SECAM
			TRAP	C	ОМВ	443	FAL	SECAIVI
(34)<35>	TINT	NTSC tint angle	FFF		A8	-	-	-
(49)<50>	L/C DELAY	Luminance/chroma delay	3		3	3	3	17
				[- -	▼ =A8 }			

Figure 1

DPMO98-024R, SENG Page 1 of 1