

Display

Date: **August 2, 1993**Model: **BVM-1316/1316C/1911/1916**Serial No: **ALL**Subject: **MONITOR CONFIGURATION FOR
BKM-1421 PAL-M DECODER BOARD****DESCRIPTION**

When defining the monitor configuration for installation of the optional BKM-1421 PAL-M decoder board, "PAL-M DECODER" should be set as "YES". In some units, even with the correct setting, the decoder may not operate properly.

If this occurs, redefine monitor configuration settings as follows:

1. Press the MENU button to display the initial menu.
2. Press the down-arrow until the cursor reaches MONITOR CONFIG, then press the ENT button.

The MONITOR CONFIGURATION menu is displayed.

3. With the cursor on OPTION INSTALLATION, press the ENT button.

The OPTION INSTALLATION 1 menu is displayed.

4. Press the down-arrow key until the cursor reaches PAL DECODER, then use the ENT button (which toggles YES/NO) to select "YES".

5. Press the down-arrow key until the cursor reaches OTHER OPTIONS, then press the ENT button.

The OPTION INSTALLATION 2 menu is displayed.

6. With the cursor on PAL-M DECODER, use the ENT button to select "YES".

7. Press the down-arrow key until the cursor reaches SAVE AND APPLY, then press the ENT button.

The message "DATA SAVED" is momentarily displayed and the monitor returns to normal status.

